



Floor Milling Machine FPE250


Working width 250 mm



Different motors: 7.5 kW electric or petrol version with 9 or 13 HP



The speed-controlled drive unit ensures consistent and even feed



Versatile and durable cutter drum assemblies

The FPE250 is the right machine to start concrete renovation and floor gutting. With a multitude of tool options, you can find a suitable solution for almost every construction site. Its main applications include removal of coatings and hard concrete, milling of grooves or joints,

texturing, scabbling, planing of concrete or asphalt surfaces. The FPE250DU and FPG250DU are equipped with their own drive unit. The feed speed is infinitely variable. The user can work fatigue-free and achieve even milling surface.



System & Accessories

Technical data

Floor milling machine	FPE250	FPE250DU	FPG250	FPG250DU
Voltage / frequency	400 V / 50 Hz	400 V / 50 Hz	Petrol	Petrol
Type no.	11002924	11002925	11002926	11002927
Working width	250 mm	250 mm	250 mm	250 mm
Power (drive motor)	7.5 kW	7.5 kW (0.2 kW)	9 HP	13 HP (0.2 kW)
Current consumption	14.8 A	16 A	-	-
Speed (drive motor)	2880 rpm	2880 rpm (3000 rpm)	3000 rpm	3600 rpm (3000 rpm)
Tool speed	1571 rpm	1571 rpm	1667 rpm	1571 rpm
Engine cooling	Air	Air	Air	Air
Vacuum connection	70 mm	70 mm	70 mm	70 mm
Application	Dry	Dry/wet (optional)	Dry	Dry/wet

Design

Height adjustment by hand wheel	•	•	•	•
Quick lift lever	•	•	•	•
Belt tensioner with durable toothed belt	•	•	•	•
Vacuum cleaner connection	•	•	•	•

Dimensions & Weight

Length	1000 mm	1000 mm	1000 mm	1070 mm
Width	490 mm	490 mm	490 mm	490 mm
Height	1130 mm	1130 mm	1130 mm	1130 mm
Weight	124 kg	150 kg	110 kg	165 kg

System & Accessories

11004005	Line Up Mechanism
11002730	Sprinkler System Complete
11004025	Exchangeable complete drum with Cutters 57/6
11004026	Exchangeable complete drum with Milling Flails 57/20
11003369	Drum for Diamond Blades
34556797	CONTEC Diamond Blade 200 mm for Hard Concrete