



Floor Stripper FRE350

Working width 350 mm



Directly driven impact mechanism – low maintenance and reliable



Ergonomically designed handle bars with control unit incl. dead man's switch



Available accessories

The FRE350 sets new standards for floor stripper performances. The extra strong design enables peeling and removing of carpets, tiles, directly bonded parquet floors, fillers and coatings. Integrated weights are

adjustable to three positions, ensuring maximum blade performance on different floor conditions, higher pressure on the drive wheels or more weight on the tool.



System & Accessories

Technical data

Floor stripper	FRE350
Voltage / frequency	230 V / 50 Hz
Type no.	11002737
Working width	350 mm
Power (drive motor)	1.5 kW (0.4 kW)
Current consumption	11.2 A
Speed (drive motor)	2790 rpm (2800 rpm)
Motor cooling	Air
Vacuum connection	40 mm
Application	Dry

Design

Lockable drive unit	•
Directly driven impact mechanism (low maintenance)	•
Height-adjustable drawbar	•
Lifting eye	•
Protective cover	•
Integrated weights adjustable to 3 positions	•
Ergonomically designed handle bars	•

Dimensions & Weight

Length	810 mm
Width	500 mm
Height	1040-1130 mm
Weight	225 kg

System & Accessories

11002738	Angle Adjustment 350 mm for Blade +/- 10 degrees
11003895	Transport Wheel Attachment Complete FRE350
11002739	Dust Support Set Complete FRE350
11004008	Service Box FRE350
11002740	Chisel Holder
11002741	Chisel 25 mm
11003888	Chisel 50 mm
11004184	Blade Weasel 230 x 80 x 1.5 mm
11003890	Blade Weasel 230 x 100 x 2.0 mm
11003892	Blade FRE250/350 200 x 80 x 2.5 mm
11003891	Blade FRE250/350 200 x 80 x 1.5 mm
11003894	Blade FRE350 450 x 80 x 2.5 mm
11002743	Blade FRE350 350 x 130 x 1.5 mm
11004014	Blade FRE350 350 x 80 x 2.5 mm
11002742	Blade FRE350 350 x 80 x 1.5 mm
11004012	Blade U-Shape Sharp FRE250/350 250 x 80 x 1.5 mm
11002744	Blade U-Shape Sharp FRE350 350 x 80 x 1.5 mm
11003889	Blade U-Shape Flat FRE350 350 x 80 x 1.5 mm
11004011	Blade FRE250/350 250 x 130 x 1.5 mm
11004013	Blade FRE250/350 250 x 80 x 2.5 mm